

PURLINE | wineo 1000 Multi-Layer to click


Long-lasting multi-layer flooring according to ISO 20326 for glueless installation

wineo

	wood L	wood XL	stone L
			
Format	1288 x 187 mm	1520 x 238 mm	636 x 319 mm
Product thickness	9 mm	9 mm	9 mm
Weight	8.70 kg/m ²	8.70 kg/m ²	8.70 kg/m ²
Profile connection	Fold-Down 	Fold-Down 	LocTec 
Planks / m² per box	8 / 1.93 m ²	6 / 2.17 m ²	9 / 1.83 m ²
Boxes / m² per pallet	44 / 84.92 m ²	48 / 104.16 m ²	60 / 109.80 m ²
Guarantee	You can find our guarantee conditions at – www.wineo.de		



Classification			Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Top element • PU-top layer with surface-structure • decor paper • stabilisation
	Utilization class 32 EN ISO 10874	Commercial sector with average usage		
	R9 Anti slip category DIN 51130	R 9		
	Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	2	Profile connection Fold-Down locking (wood) LocTec locking (stone)
	Light fastness EN ISO 105-B02	~ 7	3	Core board Swell-protected Aqua-Protect® HDF core board
	Residual indentation EN ISO 24343-1	~ 0.05 mm	4	Underlay Integrated underlay soundPROTECT
	Castor chair test EN 425	25000 revolutions no damage with rolls type W		
	Thermal resistance EN 12667	0.06 (m²K)/W	 www.blauer-engel.de/uz176	
	Sound-Protect Eco Impact sound reduction EN ISO 10140	~ 15 dB		
Reflected walking sound reduction		~ 29 %		
REACH		free from SVHC substances ≥ 0.1 %		
Disposal		<u>Private:</u> possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203		



Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.